

Key Features

- Ultra-precise writing with **50-point PCAP touch, palm rejection, and Write Away™ technology**
- Secure, future-ready performance with **upgradable Android 15 OS, EDLA certification, and octa-core processor with 16GB RAM**
- Streamlined device management with **ViewSonic Manager**
- **NFC login** for fast, secure user access in shared workspaces
- **Smart sensors** that auto-adjust brightness, monitor ambient conditions, and activate power-saving modes



Product Description

The ViewSonic® ViewBoard® IFP63 Series is a 4K UHD interactive flat panel designed for secure, high-performance collaboration in enterprise and higher education environments. With ultra-responsive 50-point PCAP touch, palm rejection, and Write Away™ technology, it enables seamless, pen-on-paper annotation—ideal for hybrid meetings, interactive lessons, and brainstorming sessions. Powered by Android 15 and EDLA-certified, the interactive display provides secure access to the latest apps and updates on a future-ready platform. An octa-core processor and 16GB of RAM support smooth multitasking for demanding workflows, while NFC tap-to-sign-in simplifies access in shared settings. Part of the ViewSonic Business Solutions, it includes three powerful software tools: Manager for remote device management, AirSync for wireless casting, and TeamOne for real-time collaboration. Designed with sustainability in mind, this display features integrated sensors that adjust brightness, monitor environmental conditions, and trigger energy-saving modes. It is certified EPEAT Gold and EEL Level F for efficient, environmentally responsible deployment.

- | | | | |
|----------------------------------|-----------------------|---------------------|---------------|
| 1. NFC | 11. Audio In | 21. USB-C 3.2 Gen 1 | 31. USB-A 2.0 |
| 2. Power | 12. USB-C Out | 22. WiFi Slot | |
| 3. USB-C 3.2 Gen 1 | 13. Audio Out | 23. Speaker | |
| 4. HDMI 4 | 14. USB-A 3.2 Gen 1*2 | 24. Power Switch | |
| 5. Touch 3 | 15. Micro SD | 25. AC In | |
| 6. USB-A 3.2 Gen 1 | 16. HDMI Out | 26. SPDIF | |
| 7. USB-A 3.2 Gen 1 | 17. Touch 1 | 27. LAN | |
| 8. USB-C 3.2 Gen1 | 18. HDMI 1 | 28. DP In | |
| 9. VESA® Wall Mount (500x400 mm) | 19. HDMI 2 | 29. RS232 | |
| 10. OPS Slot | 20. HDMI 3 | 30. Touch 2 | |

Visit Us www.viewsonic.com

DISPLAY

Panel Size:	65"
Panel Type:	TFT LCD module with DLED backlight, ADS
Display Area (mm):	1428.48(H) × 803.52(V)(64.5" diagonal)
Aspect Ratio:	16:9
Resolution:	UHD 3840x2160(Pixels)
Colors:	1.07G colors (8-bit+FRC)
Brightness:	450 nits (typ.)
Contrast Ratio:	5000:1
Response Time:	6.5ms
Viewing Angles:	H = 178, V = 178 (Typ.)
Backlight Life:	50,000hrs (Typ.)
Surface Treatment:	Pencil Hardness 9H with AG+AF+Anti-bacteria
Bezel:	31.4/31.4/38.9/64.8
Orientation:	Landscape

PLATFORM

Processor:	Octa-Core CPU (A76*4 + A55*4)
RAM:	16GB LPDDR
Storage:	128GB eMMC

TOUCH

Type/ Tech:	PCAP
Touch Resolution:	32767 x 32767
Touch Point:	Windows: 50 Android: 50
Palm Rejection:	both passive and active pens

INPUT

HDMI:	FRONT x1 (HDMI 2.1) (HDMI support CEC) REAR x3 (HDMI 2.1) (HDMI 1 support CEC, ARC) (HDMI 2.1) (HDMI 2, 3 support CEC)
DisplayPort:	1 (DP1.2)
Audio:	1 (3.5mm phone jack, mic in)
RS232:	x1
SD/SDHC:	MicroSD card slot x1
OPS:	OPS slot x1
WiFi:	WiFi slot x1

OUTPUT

HDMI:	x1 (4K@60Hz)
Audio:	x1 (Earphone out)
SPDIF:	x1 (Optical)

LAN

RJ45:	x2 (Speed: 10/100/1000Mbps, WOL supported, ProAV vendor & ViewSonic protocol supported)
-------	--

USB

Type A:	REAR x1 (USB 2.0 support OTG) REAR x2 (USB 3.2 Gen 1) FRONT x2 (USB 3.2 Gen 1)
Type B:	FRONT x1 (USB 2.0) REAR x2 (TOUCH 1: USB 3.0; TOUCH 2: USB 2.0)
Type C:	FRONT x1 (DP 1.2, touch, 100M ethernet, USB 3.2 Gen 1, smart USB 2.0, PD 65W) REAR x1 (DP 1.2, touch, 100M ethernet, USB 3.2 Gen 1, smart USB 2.0, PD 100W) Top x1 (USB 3.2 Gen 1 + PD15W to support Camera mounting)

SPEAKERS

20W x 2 + 20W x 1 (Subwoofer)

MICROPHONE

Built-in 8 Array Microphone

TOP CAMERA PLATE

Yes

COMPATIBILITY

HDMI:	3840x2160 @ 60Hz
DisplayPort:	3840x2160 @ 60Hz

EMBEDDED OS

Android 15 EDLA

BUNDLED SOFTWARE

Basic Annotation Software:	myViewBoard for Android
Pro Annotation Software:	myViewBoard for Windows (embedded in VPC)
Pro Whiteboarding Software:	TeamOne
Wireless Presentation:	AirSync
Device Management:	Manager
ViewSonic Launcher:	Yes

SPECIAL FEATURES

All-in-one USB port:	USB 3.2 Gen1 "SmartPort USB" to all channels
Simple LAN sharing between IFP and slot-in device:	(10/100/1000M) (USB Type-C 10/100, Android & PC 10/100/1000)
Light Sensor:	Yes
PIR Sensor:	Yes
NFC Reader:	Yes
Pen Sensor for supporting Write Away:	Yes
Environmental Sensor:	Temperature Sensor x1, Humidity Sensor x1, eCO2 Sensor x1, VOCs Sensor x1, PM2.5 Sensor x1

POWER

Voltage:	100-240VAC +/- 10% Wide Range
Consumption:	On: 88.5W / Off: <0.5W

ERGONOMICS

Wall Mount (VESA®):	600 x 400
---------------------	-----------

OPERATING CONDITIONS

Temperature (°C):	0°C ~ 40°C
Humidity:	20% ~ 80% RH non-condensing

DIMENSIONS (W X H X D)

Physical (inch / mm):	58.8 x 35.8 x 3.1in/ 1493.3 x 909.3 x 78.8 mm
Packaging (inch / mm):	64.1 x 40.9 x 7.3in/ 1628 x 1040 x 185 mm

WEIGHT

Net (lb / kg):	92.8lb / 42.1kg
Gross (lb / kg):	110.9lb/ 50.3kg

REGULATIONS

cTUVus, FCC, EPEAT, CE, CB, BSMI, NCC, RoHS DoC, WEEE, ErP, Flicker Free, Low Blue Light

ENERGY STAR VERSION

ES8.0

EI RATING

Level F

PACKAGE CONTENTS

- 3m power cord by ship area
- Type C cable 1.8m(USB-IF certified)
- 3m touch USB cable(USB 2.0)
- Touch pen x 2 (VB-PEN-101-2C)
- RS232 adapter
- Quick Start Guide
- Clamp x 5
- Camera Plate
- Screw x 10 (camera 2+4, wall mount 4)
- HDMI cable 3m(HDMI LA certified)
- Remote control
- AAA Battery x 2
- Compliance statement

COMPATIBLE SLOT-IN PC

VPC3X Series/ VPCF5-2A Series/ VPCF5 Series/ VPC-A31-O1

Key Features

- Ultra-precise writing with **50-point PCAP touch, palm rejection, and Write Away™ technology**
- Secure, future-ready performance with **upgradable Android 15 OS, EDLA certification, and octa-core processor with 16GB RAM**
- Streamlined device management with **ViewSonic Manager**
- **NFC login** for fast, secure user access in shared workspaces
- **Smart sensors** that auto-adjust brightness, monitor ambient conditions, and activate power-saving modes



Product Description

The ViewSonic® ViewBoard® IFP63 Series is a 4K UHD interactive flat panel designed for secure, high-performance collaboration in enterprise and higher education environments. With ultra-responsive 50-point PCAP touch, palm rejection, and Write Away™ technology, it enables seamless, pen-on-paper annotation—ideal for hybrid meetings, interactive lessons, and brainstorming sessions. Powered by Android 15 and EDLA-certified, the interactive display provides secure access to the latest apps and updates on a future-ready platform. An octa-core processor and 16GB of RAM support smooth multitasking for demanding workflows, while NFC tap-to-sign-in simplifies access in shared settings. Part of the ViewSonic Business Solutions, it includes three powerful software tools: Manager for remote device management, AirSync for wireless casting, and TeamOne for real-time collaboration. Designed with sustainability in mind, this display features integrated sensors that adjust brightness, monitor environmental conditions, and trigger energy-saving modes. It is certified EPEAT Gold and EEI Level F for efficient, environmentally responsible deployment.

- | | | | |
|----------------------------------|-----------------------|---------------------|---------------|
| 1. NFC | 11. Audio In | 21. USB-C 3.2 Gen 1 | 31. USB-A 2.0 |
| 2. Power | 12. USB-C Out | 22. WiFi Slot | |
| 3. USB-C 3.2 Gen 1 | 13. Audio Out | 23. Speaker | |
| 4. HDMI 4 | 14. USB-A 3.2 Gen 1*2 | 24. Power Switch | |
| 5. Touch 3 | 15. Micro SD | 25. AC In | |
| 6. USB-A 3.2 Gen 1 | 16. HDMI Out | 26. SPDIF | |
| 7. USB-A 3.2 Gen 1 | 17. Touch 1 | 27. LAN | |
| 8. USB-C 3.2 Gen1 | 18. HDMI 1 | 28. DP In | |
| 9. VESA® Wall Mount (800x400 mm) | 19. HDMI 2 | 29. RS232 | |
| 10. OPS Slot | 20. HDMI 3 | 30. Touch 2 | |

Visit Us www.viewsonic.com

DISPLAY

Panel Size:	75"
Panel Type:	TFT LCD module with DLED backlight, ADS
Display Area (mm):	1650.24 (H) x 928.26 (V) (74.5" diagonal)
Aspect Ratio:	16:9
Resolution:	UHD 3840x2160(Pixels)
Colors:	1.07G colors (8-bit+FRC)
Brightness:	450 nits (typ.)
Contrast Ratio:	5000:1
Response Time:	6.5ms
Viewing Angles:	H = 178, V = 178 (Typ.)
Backlight Life:	50,000hrs (Typ.)
Surface Treatment:	Pencil Hardness 9H with AG+AF+Anti-bacteria
Bezel:	31.1/31.1/38.6/63.5
Orientation:	Landscape

PLATFORM

Processor:	Octa-Core CPU (A76*4 + A55*4)
RAM:	16GB LPDDR
Storage:	128GB eMMC

TOUCH

Type/ Tech:	PCAP
Touch Resolution:	32767 x 32767
Touch Point:	Windows: 50 Android: 50
Palm Rejection:	both passive and active pens

INPUT

HDMI:	FRONT x1 (HDMI 2.1) (HDMI support CEC) REAR x3 (HDMI 2.1) (HDMI 1 support CEC, ARC) (HDMI 2.1) (HDMI 2, 3 support CEC)
DisplayPort:	1 (DP1.2)
Audio:	1 (3.5mm phone jack, mic in)
RS232:	x1
SD/SDHC:	MicroSD card slot x1
OPS:	OPS slot x1
WiFi:	WiFi slot x1

OUTPUT

HDMI:	x1 (4K@60Hz)
Audio:	x1 (Earphone out)
SPDIF:	x1 (Optical)

LAN

RJ45:	x2 (Speed: 10/100/1000Mbps, WOL supported, ProAV vendor & ViewSonic protocol supported)
-------	--

USB

Type A:	REAR x1 (USB 2.0 support OTG) REAR x2 (USB 3.2 Gen 1) FRONT x2 (USB 3.2 Gen 1)
Type B:	FRONT x1 (USB 2.0) REAR x2 (TOUCH 1: USB 3.0; TOUCH 2: USB 2.0)
Type C:	FRONT x1 (DP 1.2, touch, 100M ethernet, USB 3.2 Gen 1, smart USB 2.0, PD 65W) REAR x1 (DP 1.2, touch, 100M ethernet, USB 3.2 Gen 1, smart USB 2.0, PD 100W) Top x1 (USB 3.2 Gen 1 + PD15W to support Camera mounting)

SPEAKERS

20W x 2 + 20W x 1 (Subwoofer)

MICROPHONE

Built-in 8 Array Microphone

TOP CAMERA PLATE

Yes

COMPATIBILITY

HDMI:	3840x2160 @ 60Hz
DisplayPort:	3840x2160 @ 60Hz

EMBEDDED OS

Android 15 EDLA

BUNDLED SOFTWARE

Basic Annotation Software:	myViewBoard for Android
Pro Annotation Software:	myViewBoard for Windows (embedded in VPC)
Pro Whiteboarding Software:	TeamOne
Wireless Presentation:	AirSync
Device Management:	Manager
ViewSonic Launcher:	Yes

SPECIAL FEATURES

All-in-one USB port:	USB 3.2 Gen1 "SmartPort USB" to all channels
Simple LAN sharing between IFP and slot-in device:	(10/100/1000M) (USB Type-C 10/100, Android & PC 10/100/1000)
Light Sensor:	Yes
PIR Sensor:	Yes
NFC Reader:	Yes
Pen Sensor for supporting Write Away:	Yes
Environmental Sensor:	Temperature Sensor x1, Humidity Sensor x1, eCO2 Sensor x1, VOCs Sensor x1, PM2.5 Sensor x1

POWER

Voltage:	100-240VAC +/- 10% Wide Range
Consumption:	On: 101.1W / Off: <0.5W

ERGONOMICS

Wall Mount (VESA®):	800 x 400
---------------------	-----------

OPERATING CONDITIONS

Temperature (°C):	0°C ~ 40°C
Humidity:	20% ~ 80% RH non-condensing

DIMENSIONS (W X H X D)

Physical (inch / mm):	67.5 x 40.7 x 3.1in/ 1714.3 x 1032.4 x 79.1mm
Packaging (inch / mm):	73.3 x 45.2 x 8.9in/ 1863 x 1148 x 225mm

WEIGHT

Net (lb / kg):	123.7lb/ 56.1kg
Gross (lb / kg):	152.1lb/ 69kg

REGULATIONS

cTUVus, FCC, EPEAT, CE, CB, BSMI, NCC, RoHS DoC, WEEE, ErP, Flicker Free, Low Blue Light

ENERGY STAR VERSION

ES8.0

EI RATING

Level F

PACKAGE CONTENTS

- 3m power cord by ship area
- Type C cable 1.8m(USB-IF certified)
- 3m touch USB cable(USB 2.0)
- Touch pen x 2 (VB-PEN-101-2C)
- RS232 adapter
- Quick Start Guide
- Clamp x 5
- Camera Plate
- Screw x 10 (camera 2+4, wall mount 4)
- HDMI cable 3m(HDMI LA certified)
- Remote control
- AAA Battery x 2
- Compliance statement

COMPATIBLE SLOT-IN PC

VPC3X Series/ VPCF5-2A Series/ VPCF5 Series/ VPC-A31-O1

Key Features

- Ultra-precise writing with **50-point PCAP touch, palm rejection, and Write Away™ technology**
- Secure, future-ready performance with **upgradable Android 15 OS, EDLA certification, and octa-core processor with 16GB RAM**
- Streamlined device management with **ViewSonic Manager**
- **NFC login** for fast, secure user access in shared workspaces
- **Smart sensors** that auto-adjust brightness, monitor ambient conditions, and activate power-saving modes



Product Description

The ViewSonic® ViewBoard® IFP63 Series is a 4K UHD interactive flat panel designed for secure, high-performance collaboration in enterprise and higher education environments. With ultra-responsive 50-point PCAP touch, palm rejection, and Write Away™ technology, it enables seamless, pen-on-paper annotation—ideal for hybrid meetings, interactive lessons, and brainstorming sessions. Powered by Android 15 and EDLA-certified, the interactive display provides secure access to the latest apps and updates on a future-ready platform. An octa-core processor and 16GB of RAM support smooth multitasking for demanding workflows, while NFC tap-to-sign-in simplifies access in shared settings. Part of the ViewSonic Business Solutions, it includes three powerful software tools: Manager for remote device management, AirSync for wireless casting, and TeamOne for real-time collaboration. Designed with sustainability in mind, this display features integrated sensors that adjust brightness, monitor environmental conditions, and trigger energy-saving modes. It is certified EPEAT Gold and EEL Level F for efficient, environmentally responsible deployment.

- | | | | |
|----------------------------------|-----------------------|---------------------|---------------|
| 1. NFC | 11. Audio In | 21. USB-C 3.2 Gen 1 | 31. USB-A 2.0 |
| 2. Power | 12. USB-C Out | 22. WiFi Slot | |
| 3. USB-C 3.2 Gen 1 | 13. Audio Out | 23. Speaker | |
| 4. HDMI 4 | 14. USB-A 3.2 Gen 1*2 | 24. Power Switch | |
| 5. Touch 3 | 15. Micro SD | 25. AC In | |
| 6. USB-A 3.2 Gen 1 | 16. HDMI Out | 26. SPDIF | |
| 7. USB-A 3.2 Gen 1 | 17. Touch 1 | 27. LAN | |
| 8. USB-C 3.2 Gen1 | 18. HDMI 1 | 28. DP In | |
| 9. VESA® Wall Mount (800x600 mm) | 19. HDMI 2 | 29. RS232 | |
| 10. OPS Slot | 20. HDMI 3 | 30. Touch 2 | |

Visit Us www.viewsonic.com

DISPLAY		USB		WEIGHT	
Panel Size:	86"	Type A:	REAR x1 (USB 2.0 support OTG) REAR x2 (USB 3.2 Gen 1) FRONT x2 (USB 3.2 Gen 1)	Net (lb / kg):	143.5lb/ 65.1kg
Panel Type:	TFT LCD module with DLED backlight, ADS	Type B:	FRONT x1 (USB 2.0) REAR x2 (TOUCH 1: USB 3.0; TOUCH 2: USB 2.0)	Gross (lb / kg):	185.6lb/ 84.2kg
Display Area (mm):	1895.04 (H) x 1065.96 (V) (85.6"diagonal)	Type C:	FRONT x1 (DP 1.2, touch, 100M ethernet, USB 3.2 Gen 1, smart USB 2.0, PD 65W) REAR x1 (DP 1.2, touch, 100M ethernet, USB 3.2 Gen 1, smart USB 2.0, PD 100W) Top x1 (USB 3.2 Gen 1 + PD15W to support Camera mounting)	REGULATIONS	
Aspect Ratio:	16:9			cTUVus, FCC, EPEAT, CE, CB, BSMI, NCC, RoHS DoC, WEEE, ErP, Flicker Free, Low Blue Light	
Resolution:	UHD 3840x2160(Pixels)			ENERGY STAR VERSION	
Colors:	1.07G colors (8-bit+FRC)			ES8.0	
Brightness:	450 nits (typ.)			EI RATING	
Contrast Ratio:	5000:1			Level F	
Response Time:	8ms	SPEAKERS		PACKAGE CONTENTS	
Viewing Angles:	H = 178, V = 178 (Typ.)	20W x 2 + 20W x 1 (Subwoofer)		1. 3m power cord by ship area 2. Type C cable 1.8m(USB-IF certified) 3. 3m touch USB cable(USB 2.0) 4. Touch pen x 2 (VB-PEN-101-2C) 5. RS232 adapter 6. Quick Start Guide 7. Clamp x 5 8. Camera Plate 9. Screw x 10 (camera 2+4, wall mount 4) 10. HDMI cable 3m(HDMI LA certified) 11. Remote control 12. AAA Battery x 2 13. Compliance statement	
Backlight Life:	50,000hrs (Typ.)	MICROPHONE		COMPATIBLE SLOT-IN PC	
Surface Treatment:	Pencil Hardness 9H with AG+AF+Anti-bacteria	Built-in 8 Array Microphone		VPC3X Series/ VPCF5-2A Series/ VPCF5 Series/ VPC-A31-O1	
Bezel:	32.5/32.5/39.7/64.8	TOP CAMERA PLATE			
Orientation:	Landscape	Yes			
PLATFORM		COMPATIBILITY			
Processor:	Octa-Core CPU (A76*4 + A55*4)	HDMI:	3840x2160 @ 60Hz		
RAM:	16GB LPDDR	DisplayPort:	3840x2160 @ 60Hz		
Storage:	128GB eMMC	EMBEDDED OS			
TOUCH		Android 15 EDLA			
Type/ Tech:	PCAP	BUNDLED SOFTWARE			
Touch Resolution:	32767 x 32767	Basic Annotation Software:	myViewBoard for Android		
Touch Point:	Windows: 50 Android: 50	Pro Annotation Software:	myViewBoard for Windows (embedded in VPC)		
Palm Rejection:	both passive and active pens	Pro Whiteboarding Software:	TeamOne		
INPUT		Wireless Presentation:	AirSync		
		Device Management:	Manager		
		ViewSonic Launcher:	Yes		
		SPECIAL FEATURES			
HDMI:	FRONT x1 (HDMI 2.1) (HDMI support CEC) REAR x3 (HDMI 2.1) (HDMI 1 support CEC, ARC) (HDMI 2.1) (HDMI 2, 3 support CEC)	All-in-one USB port:	USB 3.2 Gen1 "SmartPort USB" to all channels		
DisplayPort:	1 (DP1.2)	Simple LAN sharing between IFP and slot-in device:	(10/100/1000M) (USB Type-C 10/100, Android & PC 10/100/1000)		
Audio:	1 (3.5mm phone jack, mic in)	Light Sensor:	Yes		
RS232:	x1	PIR Sensor:	Yes		
SD/SDHC:	MicroSD card slot x1	NFC Reader:	Yes		
OPS:	OPS slot x1	Pen Sensor for supporting Write Away:	Yes		
WiFi:	WiFi slot x1	Environmental Sensor:	Temperature Sensor x1, Humidity Sensor x1, eCO2 Sensor x1, VOCs Sensor x1, PM2.5 Sensor x1		
OUTPUT		POWER			
HDMI:	x1 (4K@60Hz)	Voltage:	100-240VAC +/- 10% Wide Range		
Audio:	x1 (Earphone out)	Consumption:	On: 121.1W / Off: <0.5W		
SPDIF:	x1 (Optical)	ERGONOMICS			
LAN		Wall Mount (VESA®):	800 x 600		
RJ45:	x2 (Speed: 10/100/1000Mbps, WOL supported, ProAV vendor & ViewSonic protocol supported)	OPERATING CONDITIONS			
		Temperature (°C):	0°C ~ 40°C		
		Humidity:	20% ~ 80% RH non-condensing		
		DIMENSIONS (W X H X D)			
		Physical (inch / mm):	77.2 x 46.2 x 3.1in/ 1961.9 x 1172.5 x 79.5mm		
		Packaging (inch / mm):	87 x 50.8 x 8.9in/ 2110 x 1291 x 225mm		