

DHI-PHMIA135-CF

COB Foldable All-In-One LED



Features :

- Fully flip COB module, bumping and moisture-proof;
- Folded inward screen, and the collision sensing system is built into the electric lifting bracket to effectively prevent the screen body from bumping;
- Ready to use without installation;
- Wireless screen projection, file push, reverse control screen, code sharing, brightness sensing;
- Flip camera and fingerprint unlock to ensure security and privacy.



Technical Specification

Model

Model	DHI-PHMIA135-CF
-------	-----------------

Parameters

Pixel Pitch	1.5625mm
Pixel Configuration	1R1G1B
LED Type	Flip COB 3 in 1
Brightness	600 nit (Max)
Color Temperature	9300K±200K
Viewing Angle (H/V°)	160°/160°
Pixel Density	409,600 dot/m ²
Module Size	150mm×168.75mm
Display Resolution(W×H)	1920×1080
Visible Area (H x V)	3000mm×1687.5mm
Overall Size (W×H×D)	3014mm × 2630mm × 770mm(Rise to the top) 1804mm × 1980mm × 770mm(Folding down)
Weight	513kg(Include flight case)
Display Size	135-inch
Cabinet Material	Die-cast aluminum
IP Rating	Front IP30/Rear IP30
Operating Temperature/ Humidity	-10 C~+40 C / 20%~70%RH (LED screen)
Storage Temperature/ Humidity	-10 C~+50 C / 20%~80%RH

Gray Scale	13bits
Contrast Ratio	10000:1
Refresh Rate	3840 Hz
Input Voltage	AC100~240V
Input Power (Max)	2400W(Include bracket 400W)
Input Power (Avg)	800W
Installation Mode	Free installation with lifting and moving bracket
Maintenance Mode	Front Maintenance
System / Storage Memory	8G / 64G
Control Interface	RJ45x1,RS232x1,USB 3.0x4,Bluetoothx1,Wi-Fi6x1, Light Sensorx1,Infrared Remote Controlx1
Video Interface	HDMI IN 4Kx1,HDMI OUT 4Kx1,Type-C IN 4Kx1
Audio Interface	Built-in 4x15W speakers,3.5mm Line Out x1
System	Android 11/Windows 11 (Optional)
Standard Accessories	Remote Control,Vacuum Front Maintenance Tool
Wi-Fi Standard	Wi-Fi STATION: 802.11b/g/n/a/ac/ax Wi-Fi AP: 802.11b/g/n/a/ac
Wi-Fi Frequency Range	Wi-Fi STATION: 2400-2483.5MHz, 5150-5250MHz , 5250-5350MHz, 5470-5725MHz, 5725-5850MHz WIFI AP: 2400-2483.5MHz,5150-5350MHz
Wi-Fi MAX Transmission Power	≤20dBm@2400-2483.5MHz;≤23dBm@5150-5250MHz; ≤20dBm@5250-5350MHz;≤27dBm@5470-5725MHz; ≤14dBm@5725-5850MHz
Bluetooth Standard	BR/EDR/BLE(Bluetooth mode), BT5.0(Bluetooth version)
Bluetooth Frequency Range	2400-2483.5MHz
Bluetooth MAX Transmission Power	≤20dBm@2400-2483.5MHz

DHI-PHMIA135-CF

COB Foldable All-In-One LED

