

UHZ68LV

Bright 4K UHD Dual Laser home entertainment projector



- **4K UHD dual-laser technology - Immerse yourself in stunning visuals with 5000 lumens and 95% DCI-P3 colour accuracy**
- **Powered by Dolby Vision® and HDR10+ - Experience cinema-quality picture with incredible brightness, contrast, and colour**
- **PureEngine™ Ultra - Enjoy smooth motion, sharp details, and customised picture settings**
- **Flexible Installation - Adapt to any space with 1.6x zoom, lens shift, and 360-degree projection**



Elevate your home entertainment with the Optoma UHZ68LV 4K UHD Projector. Powered by Dolby Vision® and HDR10+ technologies, this dual-laser projector delivers stunning picture quality with incredible brightness, contrast, and colour accuracy.

Enjoy smooth motion, sharp details and customised picture settings with PureEngine™ Ultra. Watch films as the director intended with Filmmaker mode. Plus, with flexible installation options and long-lasting performance, the UHZ68LV is the perfect choice for any home cinema enthusiast.

Specifications

UPC: 796435 81 530 1, EAN: 5055387668652 , Colour: Black



Display/Bild	
Display Technologie	DLP™
Auflösung	UHD (3840x2160)
Helligkeit	5.000Lumen
Kontrastverhältnis	3.200.000
Bildseitenformat	16:9
Kompatible Bildformate	4:3,16:9
Keystone Korrektur - horizontal	+/-30°
Keystone Korrektur - vertikal	+/-30°
Horizontale Scan Rate	15 ~ 255Khz
Vertikale Scan Rate	24 ~ 240Hz
Uniformität	85%
Leinwandgröße	0.78m ~ 7.65m (30.6" ~ 301.1") diagonale
Lampentyp	
Lichtquelle	Laser
LASER Lebensdauer	30.000Stunden
Optik	
Projektionsverhältnis	1.2:1 ~ 1.92:1
Projektionsabstand (m)	1m - 10m
Zoom	1.6
Zoom Typ	Manuell
Brennweite (mm)	17.63mm~27.88mm/0.694"~1.097"
Lens Shift	Vertikal -106 ~ 126%, Horizontal --10 ~ 10%
Native Offset	126%
Lens Shift	Ja - see product downloads for more information
Anschluss	
Anschlüsse	Anschlüsse 1 x HDMI 2.1, 2 x HDMI 2.0 (eARC) Ausgänge 1 x USB-A Power 1,5A, 2 x USB-A Power 0,9A, 1 x 3D Sync, 1 x Audio 3.5mm, 1 x S/PDIF Steuerung 1 x RJ45, 1 x RS232, 2 x 12V Trigger
Generelle Infos	
Betriebsgeräusch ECO	25dB
Betriebsgeräusch (max)	31dB
3D	Full 3D
Sicherheit	Sicherheitsbefestigung, Kensington Lock, Passwortgeschützte Schnittstelle
OSD / Display Sprachen	25 Sprachen: Arabisch, Tschechisch, Norwegisch/Dänisch, Niederländisch, Englisch, Farsi, Finnisch, Französisch, Deutsch, Griechisch, Ungarisch, Indonesisch, Italienisch, Japanisch, Norwegisch, Polnisch, Portugiesisch, Rumänisch, Russisch, Chinesisch (vereinfacht), Spanisch, Schwedisch, Chinesisch (traditionell), Türkisch, Vietnamesisch
24/7 Betrieb	Ja
360° Darstellung	Ja
Betriebsbedingungen	0°C~40°C/32°F~104°F, max. altitude 3,048m/10,000ft, max. humidity operating 80%, non-operating 90%
Lautsprecher	2
Watt pro Lautsprecher	5W
Eingangsverzögerung	8.50ms
Netzwerk	
LAN - Steuerung	Ja
Stromverbrauch	
Stromversorgung	100 ~ 240V, 50 ~ 60Hz
Stromverbrauch (standby)	0.5W
Stromverbrauch (min)	165W
Stromverbrauch (max)	345W
Gewicht und Maße	
Abmessungen (B x T x H) (mm)	498 x 331 x 171
Gross weight	11.8 kg
Net weight	9.2 kg